

GPM Cooling Capacity at Indicated Operating Conditions

			Range (deg.F.)	10	10	15	20	20	10	10	15	20	20
			Approach (deg.F.)	5	7	7	9	12	5	7	5	7	10
			Wet Bulb (deg.F.)	78	78	78	78	78	82	82	82	82	82
Model	No. Fans	Total HP											
TTRT-101975	10	75	2630	3321	2712	2858	3500	2945	3500	2438	2691	3466	
TTRT-101950	10	50	2316	2928	2389	2519	3148	2596	3264	2146	2371	3058	
TTRT-101930	10	30	N/A	2498	2035	2146	2688	2212	2787	N/A	N/A	2464	

			Range (deg.F.)	10	10	15	20	20	10	10	15	20	20
			Approach (deg.F.)	8	10	10	12	16	7	10	9	10	14
			Wet Bulb (deg.F.)	70	70	70	70	70	74	74	74	74	74
Model	No. Fans	Total HP											
TTRT-101975	10	75	2965	3500	2833	2856	3500	2982	3500	2913	2760	3500	
TTRT-101950	10	50	2614	3123	2497	2517	3238	2628	3462	2567	2432	3207	
TTRT-101930	10	30	2228	2666	2127	2145	2764	2240	2956	2187	2072	2737	

			Range (deg.F.)	10	10	15	20	20
			Approach (deg.F.)	10	15	15	15	20
			Wet Bulb (deg.F.)	64	64	64	64	64
Model	No. Fans	Total HP						
TTRT-101975	10	75	3040	3500	3422	2945	3500	
TTRT-101950	10	50	2681	3500	3019	2596	3422	
TTRT-101930	10	30	2285	3276	2576	2213	2923	